

## **AAHA XHOW**

- nom perroi, or gas cylinders. a danger of explosion. It will ignite fumes Do not use a rotary hammer where there is ٠ι
- and that no-one is near to you or could Make sure that the area is clear and safe .s
- the rotary hammer is being used with an exclusion zone around the area where Protect other people from the dust. Set up 31 not logilar
- Juamqiupa sidi pnisu Keep children and animals away when physical barriers, barrier tape and signs.
- with the work, enter the exclusion zone. anyone, other than those directly assisting Work should stop immediately should ·•
- rubble, rubbish etc. Clear the area of trip hazards such as
- Do not use a rotary hammer in the rain or
- amount of dust cover any surfaces or Drilling certain materials makes a large .7 .າອຸທ າອຸຽ າມຸຽແມ າເ ອາອຸມໜ
- objects that may be damaged, or difficult to

### **SROTAR390** :upaid

- should be worn whenever you use this machine. Particular jobs or environments equipment (PPE) are the minimum that The following items of personal protective ٦.
- You will need to wear an appropriate dust ·7 may require a higher level of protection.
- protection) when you are in contact with mask (with a minimum of EN149:2001FFP3
- You must wear safety boots (EN345 or material that causes dust.
- ·(Z/6t/0/8LSB
- You must wear industrial quality gloves.

- vesociation ⊨urope

# มกอา ระบอดอา กระ





v:032017









·9

·+

31

•z

-1

'G



Adjust it to the best position.

. Buld issues of the second s

0503 Safety Guidance

It is important to read all of this leaflet

**BEFORE you use the Rotary Hammer** 

Electricity is dangerous and must always be used with great

This rotary hammer is designed for drilling in concrete,

The action of this rotary hammer can cause injury or damage if

the machine is not used in a careful and controlled way.

straightforward work before you start on the main task

**Rotary Hammer** 

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

If you have not used a rotary hammer before, familiarise yourself with the machine on some

You must have at least the following items of personal protective equipment: goggles:

EN166 or BS2092; dust mask - a minimum of EN149 FFP3(s) protection; Safety boots to EN345 or BS1870/4972; industrial quality gloves; residual-current device (RCD) if using a

A rotary hammer must not be used by minors, or by anyone under the influence of drugs or

A rotary hammer is designed for operation by an able bodied adult. Anyone with either

Although rotary hammer are designed for one person operation you should always be

ty enotinable been made by here renate the intermediation given in this document and supporting is accurate and not misleading. HAE/ENA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments

have the force of law and only the courts can authoritatively interpret the law.

temporary or permanent disability must seek expert advice before using it.

effort has been made by HAE/EHA to ensure that the information given in this docum

Plan your work and think ahead to make sure you will always be working safely.



































Always use the side handle provided.

either a normal square pin plug fitted, or a

to run directly from 230v mains will have

yourself when moving it about - it may be heavier than you think. Machines designed

been supplied, take care not to injure

230v supply. It a portable transformer has

to power the machine from a normal mains

provided a portable transformer if you need

supply. The hire company will have

plug fitted are designed to run off an 110v

Machines with a cylindrical yellow industrial

Check that the plug on your machine matches your supply. Do not try to force

not use the rotary hammer - contact the

drill bits. If anything is found damaged, do

Check your machine, cables, plugs and

also need to wear identical personal

Anybody who is working near to you will

connections or improvise them.


nre company.

ЯЗММАН ҮЯАТОЯ

protective equipment.



## - Udrs .on teltsel HAH ent to yqoo working. Ask the hire company for a keep your hands warm while you are perore you start work, and wear gloves to



will be 110v or 230v.

**YTERCAL SAFETY** 

slot or taper fixing.

1.

2.

4.

8

9

10

alcohol

care.

masonry or brickwork

230 volt (mains) supply.

A personal first-aid kit should be available.

careful you do not lift beyond your own capabilitie

It you are using a portable transformer, plug

square pin plug fitted, or a blue industrial plug.

fitted. 230v machines will have either a normal

110v machines will have a yellow industrial plug

Your machine will only operate on one voltage: it

specifically for this rotary hammer. You

3. You must only use the correct drill bits

2. This machine uses special drill bits with a

Switch the rotary hammer off, and unplug it

ρειοιε γου switch the rotary hammer on,

Check on how the on/off switch operates -

vibration

must not use any other drill dits.

before changing the drill bit.

you must know how to stop it.

www.hse.gov.uk/vibration

110 VOLT MACHINES (YELLOW PLUG)

Read the instructions below for your machine

121 380 4600

e.org.uk www.hae.org.uk

44 (0) 121 333 4109

- a suitably rated heavy dury 110v extension any special instructions, you should only use company. If the hire company has not given αυλ εbecial instructions given by the hire
- extension cable > rotary hammer. 230v: Wall socket > RCD > any necessary
- ssary extension cable > rotary hammer. suλ 110V: Wall socket > transformer > :Lieuuns
- connections are dry and sate. 5. Make sure that any extension cable
- conid catch life. run over it. Unroll it fully or it will overheat and edges, doorways or windows where it might be trapped, and places where vehicles might 4. Lay it out carefully avoiding liquids, systb
- The HCD. than 50 metres (160 feet). Plug it directly into any special instructions, you should only use a suitably rated heavy duty one, not longer
- company. If the hire company has not given any special instructions given by the hire 3. If you need to use an extension cable, tollow .ti dtiw
- RCD according to the instructions supplied working each time you use it. Reset the 2. Use the "TEST" button to check that the RCD machine gets damaged.
- you against electric shock if the cable or machine into the RCD. This will help to protect directly in to the 230volt socket. Plug your 1. Use a residual current device (RCD) plugged
  - (золяве ыи ов вгле ргле)
    - 230 VOLT MACHINES
- connections are dry and sate. 4. Make sure that any extension cable
  - overheat and could catch fire.
- vehicles might run over it. Unroll it fully or it will where it might be trapped, and places where liquids, sharp edges, doorways or window 3. Lay the extension cable out carefully avoiding
- between the transformer and the machine. on must only use an extension cable cable, not longer than 50 metres (160 feet).

1

-9

סאורר פונג





















тала-агт

Before Starting Work.

oL

1151A

6.

7.

8.

9

unattended

hire company.

## Using the Rotary Hammer

For guidance on managing

construction health risks go to www.hse.gov.uk/construction

- Wear your protective equipment including ear defenders and goggles. 1.
- Never attempt to enlarge a hole that you have already drilled the bit will jam.
- 2. Check on the biggest drill that your machine can use - if you overload it, the bit 3. may jam, causing the drill to start to rotate. This can cause serious hand or wrist
- injury. Watch out for signs that vibration may be affecting your hands. If your fingers start 4. to tingle or feel numb, take a short break from using the machine. Exercise your fingers to encourage blood circulation. Ask the hire company for a copy of the HAE leaflet no. 2150 - Hand-arm vibration or visit www.hse.gov.uk/vibration
- To help prevent vibration affecting your hands, operate the machine for shorter 5. periods. Keep your hands warm - wearing gloves may help do this.

If you think the cable may be cut or damaged in any way, switch off and unplug

at the mains before inspecting it. If the cable attached to the rotary hammer is

damaged, stop using the machine. Contact the hire company. If an extension

Switch off and remove the plug from the socket before leaving the rotary hammer

10. If your equipment does not work properly do not attempt to repair it. Contact the

11. You may want to read this leaflet again. Please keep it until you finish work.

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

Keep the cable clear of the tool bit and any sharp edges on your work.

cable has been damaged, do not use it again.

2450 Regents Court

lihull B37 7YE

The C

Take care not to accidentally pull the plug from the socket.