

WORK AREA

- fumes from petrol or gas cylinders. there is a danger of explosion. It may ignite Do not use electrical equipment where -1
- Keep electrical equipment away from rain
- distraction. Warn others to keep away; that no-one can come close to cause Ensure the work area is clear and safe and 3 and water.
- heater, and can cause paper and cloth to ignite. Check that no loose paper or s much heat as a 1kw electric radiant near to the lights. Some lights can produce Ensure there are no combustible materials . necessary. ραιμείε οι Μαιμιό είδης μαλ ρε
- be be safe from vehicles, people, water, Set up the lights in an area where they will **.** ک rubbish can be blown close to the light.
- over. The ground should be firm and level. миси шау аатаде тет ог клоск тет rain, strong gusts of wind and other hazards
- ot form a tripping hazard in doorways or them, and so that the cables themselves do Lay out the cables to avoid damaging -9

- THOLI S'ABABTSAJA мякмаус

- ΤΗΘΙΊ ΞΊΒΑΤΑΟΥΖΝΑΗ
- found damaged, do not use it contact the supports the light properly. It anything is plugs and sockets; check that the stand Check the equipment including cables
- Check that the plugs on the cables match **'**Z nite company.
- plug fitted are designed to run off a special Lights with a cylindrical yellow industrial or improvise them. the supply. Do not try to force connections
- 110v supply. The hire company will have
- d a portable transformer if the lights

uthoritatively interpret the law

2450 Regents Court The Crescent Birmingham Business Park Solihull B37 7YE

www.use.org.uk vensue. เมฆเติมชุย.org.uk :lism3 .euoydəjə

- this is permissible.

- nniess you nave specific instruction that

- 44 (0) 121 380 4600 44 (0) 121 333 4109

1.

2.

3.

4.

6.

7

rain



31

·7

.S

·{iddns



drugs or alcohol.



Email

Plug the

Sh.

For more information on

HSE

Take care not to trap fingers when erecting the stands

halogen lights allow to cool a short while before moving.

inspect them every week to make sure that they are safe.

can cause temporary blindness.

supply before inspecting it.

powerful and hot lights.

the drop in lighting levels.

om HAE by Power Tool Rentals Ltd. Docu

Using the Plasterer's Light (transportable light)

Ensure that nobody is looking into the light before switching it on - the brightness

If a cable appears to be cut or damaged in any way, switch off and unplug the

If the cable attached to a light is damaged, stop using the light. Contact the hire

Ensure that no combustible material, such as paper or rubbish, is too close to

Switch off lights and unplug before moving them or adjusting their position. With

Before switching off any lighting, ensure no one is going to be put in danger by

11. If the lights are left in place for more than a week, then a competent person should

12. If your equipment does not work properly, do not attempt to repair it. Contact the

Please keep this leaflet safely as it may be required for reference at a future date

company. If an extension cable has been damaged, do not use it again.

Switch off and unplug before leaving the transportable lights unattended.

Do not hang or drape cables, strings or anything else over the lights.

Check that cables are laid out safely and are not causing a hazard.

health and safety in construction go to

www.hse.gov.uk/construction/

2450 Regents Court The Crescent irmingham Business Park olihull B37 7YE



hire company.

밄

1.

2.

3.

4. 5.

6.

7.

8

Copyright Hire Association Europe April 2000

Any unauthorised reproduction - manually or electronically - is STRICTLY prohibited

working each time it is used. Reset the rod 2. Use the "TEST" button to check that the rcd is

directly into the 230 volt socket.

(золяте рім ор віле ріла)

cable connections are dry and

will overheat and could catch

d. Ensure sure that any extension

against electric shock if the cable or lights get

lighting into the rcd. This will help to protect

vehicles might run over it. Unroll it tully or it

where it might be trapped, and places where

liquids, sharp edges, doorwarys or windows

extension cable between the transformer and

longer than 50 metres (160 teet). Only use an

rated heavy duty 110v extension cable, no

any special instructions only use a suitably

company. If the hire company have not given

special instructions given by the

Do not use any 230v extension cable

110 VOLT LIGHTING (YELLOW PLUG)

ELECTRICAL SAFETY - GENERAL

2. If an extension cable is required, follow any

If using a portable transformer, plug the transformer directly into the 230 volt socket.

it will be 110v or 230v. Read the instructions

The equipment will only operate on one voltage:

3. Lay the extension cable out carefully avoiding

1. Use a residual current devise ("rcd") plugged

. baganaged.

230 VOLT LIGHTING

.buitdpil ad

pelow tor each type.

TILE.

e.ora.uk whae.org.uk

and switched on – powerful lights can dazzle. 7. Do not look into the light as it is plugged in

- secure any screws or clips. replace all covers and guards properly, and 6. When the tube or bulb has been changed,
- ille; use clean cloth or lissue paper. with bare fingers - this will shorten the bulb's
- 5. Do not touch replacement halogen bulbs tixing screws or clips.
- 4. Open any covers taking care not to lose any
- ghts to cool down before safely handling 3. It may be necessary to wait for high power
- off and unplug the faulty light.
- when switching off several lights. Then switch
- 2. Ensure that no-one will be put in danger if
- fluorescent tube or halogen bulb ready. Check with the hire company if in any doubt. 1. Make sure you have the correct replacement

TUBES OR HALOGEN BULBS

CHANGING FLUORESCENT

are dry and sare

extension cable connections guì 2. Make sure that

and could catch fire. Unroll it tully or it will overheat

vehicles might run over it. trapped, and places where

εαθεε' ασοινικλε οι μισανε μηθιε με μισμε 4. Lay it out carefully avoiding liquids, sharp

Flug it alrectly into the rca.


duty one, no longer than 50 metres (160 feet) hire company have not given any special instructions, only use a suitably rated heavy required, follow any special recompany. If the instructions given by the hire company. If the

 \subset 3. If an extension cable is

nu unw peuddos according to the instructions







the hire company or labels attached to the

addition tollow any verbal instructions from

The guidance in this leaflet still applies; in

utomatically provide up to 3 hours f safety

iuw ing fiddes suieu no soni filemon

The light may be a tail-sate light that

used in a place where there is no mains

charged from a mains supply before it is

The light may be a portable light that is

Equipment designed to run directly from

not to injure yourself when moving it about

transformer has been supplied, take care

are required to be powered from a normal

If a portable

Before Starting Work

LIGHTS WITH BATTERY BACKUP

- it may be heavier than you think.


mains 230v supply.

230v mains will have either a normal squ pin plug fitted, or a blue industrial plug.

light should the mains supply tail.

- a chain of lights. single units, or to be linked together to torm
- adding more units than the maximum Do not overload the electrical system by
- stated. If unsure ask the hire company.
- Do not plug a power tool into the light chain





they are easily adjustable and quickly transportable.

RCD if using a 230 volt (mains) supply

The following items of personal protective equipment are a minimum:

temporary or permanent disability must seek expert advice before using it.



may occur so they can be dealt with safely. Electricity is hazardous and must always be used

1025 Plasterer's Light

Plasterer's Light

and similar lights

Tasklight - Contractor's Light

Failsafe Light – Upright Light

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment. This leaflet is not a substitute for a properly executed risk assessment.

with great care. Water and electricity make a very hazardous

These lights are designed to provide almost shadow free illumination on walls and ceilings;

These lights must not be installed or used by minors, or by anyone under the influence of

These lights are designed for installation and use by an able bodied adult. Anyone with either