

Before Starting Work.

AAHA XHOW

- danger of explosion. It will ignite fumes Do not use this router where there is a
- and that no-one is near to you or could Make sure that the area is clear and safe nom petrol, or gas cylinders.
- Protect other people from the noise and 31 distract you.
- Do not use this router in the rain or where °t partiers around your work area. dust. Warn others to keep away, put

it might get wet.

SROTAR340

- environments may require a higher level you use this machine. Particular jobs or minimum that should be worn whenever protective equipment (ppe) are the The following items of personal
- You must wear goggles (EN166 B or .s or protection.
- This router is likely to cause noise levels 3 with this router. BS2092 grade 1) when you are working
- tor this level as a minimum. muffs or plugs giving hearing protection up to 94 dB(A) - wear appropriate ear
- protection) when you are sanding mask (with a minimum of EV149 FFP3(s) You will need to wear an appropriate dust ·+
- also need to wear appropriate personal Anybody who is working near to you will 'G material that causes dust.

protective equipment.

ent and Statutory Instruments

.Vinbding. do not use the fourer - contact the hife cutters. It anything is tound damaged, Check your machine, cables, plugs and 1 натори

noo sinegen uce vesociation ⊨urope

3YT TEB Iludilos The Crescent Birmingham Business Park

:lism3

CUTTERS

.9014

-9

·+

31

.S.

is accurate and not misleading. HAE/EHA cannot accept responsibility for any to have arisen from the use of any such document/material. Only Acts of Parliament

0412 Safety Guidance

It is important to read all of this leaflet

BEFORE you use the Router

1. Plan the use of the Router so that it can always be used safely.

Electricity is dangerous and must always be used with great

This router is designed to cut grooves, bevels, and profiles in

wood and plastic using various guides and templates

straightforward work before you start on the main task.

permanent disability must seek expert advice before using it.

Router

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

The action of this router can cause injury or damage if the machine is not used in a careful

If you have not used a router before, familiarise yourself with the machine on some

You must have at least the following items of personal protective equipment: goggles:

EN166 or BS2092; dust mask - a minimum of EN149 FFP3(s) protection; ear muffs or plugs giving protection for levels up to 101dB (A); gloves; rcd if using a 230 volt (mains) supply.

This router must not be used by minors, or by anyone under the influence of drugs or

This router is designed for operation by an able bodied adult. Anyone with either temporary or

have the force of law and only the courts can authoritatively interpret the law.

vyse.org.u

nust know how to stop it.

damage your cutter.

changing the cutter.

ail@hae.org.uk



effort has been made by HAE/EHA to ensure that the inform























socker belore making adjustments or

store you switch the router on, you

Check on how the on/off switch operates

Keep the cable well away from the cutter.

brojections in your wood, which could

Check that there are no nails or other

suonid be securely clamped or held in a

Any work that is not part of a fixture

will have either a normal square pin plug

designed to run directly from 230v mains

yourself when moving it about it may be

been supplied, take care not to injure

supply. If a portable transformer has

machine from a normal mains 230V

transformer if you need to power the

company will have provided a portable

industrial plug fitted are designed to run off a special 110v supply. The hire

Routers with a cylindrical yellow

matches your supply. Do not try to force

Check that the plug on your router

connections or improvise them.

Machines

titted, or a blue industrial plug.

heavier than you think.

1. Switch off and remove the plug from the





2.

3.

7.

8

alcohol.

and controlled way.



Eh.



.DOT

31

'Z

ure



The C lihull B37 7YE





connections are dry and sate.

2. Make sure that any extension capie

vehicles might run over it. Unroll it fully or

might be trapped, and places where

edges, doorways or windows where it

metres (160 feet). Plug it directly into the

heavy duty one, not longer than 50

you should only use a suitable rated

the red according to the instructions

rcd is working each time you use it. Reset

Use the "TEST" button to check that eth

against electric shock if the cable or

into the rcd. This will help to protect you

5

TIT BE

मा

suy special instructions,

company have not given

hire company. If the hire

instructions given by the

cable, tollow any special

It you need an extension

machine get damaged.

socket. Plug your machine

directly in to the 230 volt

device ("rcd") plugged

connections are dry and sate.

4. Make sure that any extension cable

it. Unroll it tully or it will overheat and

and places where vehicles might run ove

or windows where it might be trapped,

avoiding liquids, sharp edges, doorways 3. Lay the extension cable out caretully

1. Use a residual current

(געטאאד פוא סא פרטב פרטפ)

230 VOLT MACHINES

conia carcu lire.

ti utiw pailqqus

4. Lay it out carefully avoiding liquids, sharp

it will overheat and could catch fire.









www.hae.org.uk

and the machine.

extension cable between the transformer

metres (160 feet). You must only use an

extension cable, not longer than 50

a suitably rated heavy duty 100v

special instructions, you should only use

230volt socket. Do not use any 230v

plug the transformer directly into the

If you are using a portable transformer

Read the instructions below for your machine.

square pin piug inted, or a blue industrial plug.

titted. 230v machines will have either a normal

Your machine will only operate on one

pulg laintsubui wollow a yellow industrial plug

direction, follow the instructions supplied

Some cutters will only cut in one

Ensure the cutter is tightened securely

Make sure you use the correct type of

company for the material being cut.

cutter recommended by the

company have not given any

the hire company. If the hire

special instructions given by

extension cable, tollow any

(110 VOLT HEATERS (YELLOW PLUG)

voltage: it will be 100v or 230v.

If you need to use an

extension cables.

YTERCAL SAFETY

with the cutters.

perore use.

31

.2

.S.

©Copyright Hire Association Europe April 102

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

14. You may want to read this leaflet again. Please keep it until you finish work. Please keep this leaflet safely as it may be required for future reference

company.

13.

Wear your protective equipment including ear defenders, dust mask and goggles. Check that there are no nails, screws or metal embedded in your wood, which could damage your cutter.

For guidance on managing

construction health risks go to www.hse.gov.uk/construction

Using the Router

3. Check that the cutter is fitted correctly.

1.

2

- Let the router run up to full speed before lowering it carefully into the wood. 4
- Stop the machine and unplug before making any adjustments. 5.
- 6. Remove any spanners or tools used for adjustment before switching on.
- Keep the cable clear of the cutter. 7.
- 8. If you think that the cable may be cut or damaged in any way, switch off and unplug at the socket before inspecting it. If the cable attached to the router is damaged, stop using the machine. Contact the hire company. If an extension cable has been damaged, do not use it again
- 9. Take care not to accidentally pull the plug from the socket.
- **10.** Switch off and wait for the cutter to stop completely before you put the router down. 11. Make sure that any ventilation slots in the router do not get blocked with sawdust.

12. Switch off and remove the plug from the socket before leaving the router unattended.

If your equipment does not work properly do not attempt to repair it. Contact the hire