



# Using the Tacker

1. Personal protective equipment must be worn including ear defenders, goggles and gloves..
2. Before switching on check that the magazine is fully loaded with choice of fasteners.
3. Make sure that nails are not going to be driven into hidden electric cables or gas pipes.
4. Do not use this tacker on brittle surfaces like hard plastics, they may crack and shatter.
5. When working two hands should always be used to guide the tacker.
6. As a safety measure, the tacker will not operate until the ejection point is depressed home against the workpiece before pulling the trigger.
7. The tacker should never be pointed at anyone nor should nails be fired at anyone. Nails should not be fired into hands.
8. Switch off the machine and unplug before making any adjustments or loading nails into the magazine.
9. Keep the cable clear of the tacker and any sharp edges on the work.
10. If operators think that the cable may be cut or damaged in any way they should switch off and unplug at the mains before inspecting it. If the cable attached to the tacker is damaged, the machine should be stopped. Contact the hire company. If an extension cable has been damaged it should not be used again.

Please keep this leaflet safely as it may be required for future reference



Hire Association Europe  
2450 Regents Court  
The Crescent  
Birmingham Business Park  
Solithull B37 7YE

Telephone: 44 (0) 121 380 4600  
Fax: 44 (0) 121 333 4109  
Email: [mail@hae.org.uk](mailto:mail@hae.org.uk)  
website: [www.hae.org.uk](http://www.hae.org.uk)

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

1. Do not use this tacker where there is a danger of explosion, or gas cylinders, turns from petrol, or gas cylinders. Make sure that the area is clear and safe and that no-one is nearby who could cause a distraction.
  3. Protect others from noise and danger. Warm others to keep away. Check that there are no hidden electric cables or gas pipes where the tacker is to be used.
  5. This tacker must not be used in the rain or where it might get wet.
- OPERATORS**
1. The following items of personal protective equipment (PPE) are the minimum that should be worn whenever this machine is used. Particular jobs or environments may require a higher level of protection.
  2. Goggles should be worn when using this machine.
  3. This equipment is likely to cause noise levels up to 98 dB(A) – appropriate ear muffs or plugs must be worn giving protection up to this level as a minimum.
  4. It may be more comfortable to wear gloves to help absorb the impact when the tacker is fired.
  5. Anybody who is nearby will also have to wear personal protective equipment.
- TACKER**
1. Check the machine, cables and plugs. If anything is found to be damaged, do not use the tacker – contact the hire company.
  2. Check that the plug on the machine matches the available supply. Connections must not be forced or improvised.
  3. Machines with a cylindrical yellow industrial plug fitted are designed to run off a special 110v supply. The hire company will have provided a portable transformer if the machine needs to be powered from a normal mains 230v supply.
- TACKS, NAILS AND STAPLES**
1. Nails should never be fired into hands; they will penetrate even through gloves.
  2. Check on how the machine works – before switching the machine on – operators must know how to control it. If an extension cable is needed, follow any special instructions given by the hire company. If the hire company have not given any special instructions, only a suitably rated heavy duty cable, not longer than 50 metres (166 feet) should be used. It should be plugged directly into the extension cable should be laid out carefully avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. It should be fully unrolled or it will overheat and could catch fire.
  4. The extension cable must be laid out carefully avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. It should be fully unrolled or it will overheat and could catch fire.
  5. Extension cable connections must be kept dry and safe.
- 230 VOLT HEATERS (SQUARE PIN OR BLUE PLUG)**
1. Use a residual current device (RCD) plugged directly into the 230 volt socket. Plug the machine into the RCD. This will help to protect against electric shock if the cable or machine get damaged.
  2. Use the "TEST" button to check that the RCD is working each time the machine is used. Reset the RCD according to the instructions supplied with it.
  3. If an extension cable is needed, follow any special instructions given by the hire company. If the hire company have not given any special instructions, only a suitably rated heavy duty cable, not longer than 50 metres (166 feet) should be used. It should be plugged directly into the extension cable should be laid out carefully avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. It should be fully unrolled or it will overheat and could catch fire.
  4. Extension cable connections must be kept dry and safe.
- 110 VOLT HEATERS (YELLOW PLUG)**
1. If using a portable transformer, plug the transformer directly into the 230v socket. 230 v extension cables should not be used.
  2. If an extension cable is needed, follow any special instructions given by the hire company. If the hire company have not given any special instructions, only a suitably rated heavy duty cable, not longer than 50 metres (166 feet) should be used. The extension cable must be used with the hire company.



## Before Starting Work...

# Tacker

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read all of this leaflet

BEFORE you use the Tacker



1. Read this entire leaflet before using the Tacker.
2. Electricity can be hazardous and must always be used with great care.
3. This tacker is designed to drive nails into wood, chipboard and similar materials. It will also drive in staples.
4. The action of this tacker can cause injury or damage if the machine is not used in a careful and controlled way.
5. If operators have not used a tacker before, they should practice with the machine on some scrap wood before starting on the actual job.
6. The work should be planned ahead and thought out to make sure that it is always carried out safely.
7. The following items of personal protective equipment must be worn:  
Goggles  
Ear muffs or plugs  
Gloves  
Rcd if using a 230 volt mains supply.
8. This machine must not be used by minors, or by anyone under the influence of drugs or alcohol.
9. This tacker is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Telephone: 44 (0) 121 380 4600  
Fax: 44 (0) 121 333 4109  
Email: [mail@hae.org.uk](mailto:mail@hae.org.uk)  
website: [www.hae.org.uk](http://www.hae.org.uk)

Hire Association Europe  
2450 Regents Court  
The Crescent  
Birmingham Business Park  
Solithull B37 7YE

