

Please keep this leaflet safely as it may be required for future reference

©Copyright Hire Association Europe 2021

Any unsuffortised reproduction – manually or electronically – is STHICILY prohibited

3

3

.S.

op paßeuro

100 OF 230V

ELECTRICAL SAFETY

Email:

vehsite

2450 Regents Court

lihull B37 7YE

OR 16 AMP BLUE PLUG)

The C

(Continued overle

Whenever possible avoid the use of extension cables with an extension cable is required, follow any special fit an extension cable is required, follow any special instructions given by the him recompany instructions, only a suitably rated heavy duty extension cable should be used, no longer in length than that specified by

clicult breaker (RCCB) should be used, plugged into the RCD. This will help protect against electric shocks if the cable or equipment gets electric shocks if the cable or equipment gets.

A residual-current device (HCD) or residual-current

Make sure that any extension cable connections ar dry and safe.

The extension cable must be laid out carefully wording any inductias, stamp edges, donoways or windere it might be run over by vehicles. It should be unoted thight be run over by vehicles. It should be monitole dulty or it will overhast and masy catch fire. Make sure that any extension cable connections are

Show may special interfactors, only a suitably rated heavy given may special interfactors and a suitably rated heavy be longer than that specified by the manufacturer or as advised by the Hire Company. The extension rache must devised by the Hire Company. The extension rache must advised by the Hire Company. The extension rache must the extension rache must be laid out carefully.

If an extension cable is required, follow any instructions given by the hire company. If the hire company has not

the portagonal of the protocol of the second of the S30v second of the S30v second of the second of

110v equipment will have a yellow industrial plug fitted. Sdv equipment will have either anomal agree pin plug, fitted, or a blue industrial plug. The instructions more must be read before using the equipment.

e floor cleaner will only operate on one voltage: it will be

110 VOLT MACHINES (YELLOW PLUG)

according to the instructions supplied with it. The 'TEST' button should be used to check that the RCD is working each time it is used. The RCD should be reset

230 VOLT MACHINES (13 AMP SQUARE PIN



0819 Safety Guidance



the manufacturer or as advised by the Hire Company. It should be plugged directly into the BCD

- The cable should be laid out carefully avo liquids, sharp edges, doorways or windows where it might be trapped, and places where it may be run over by vehicles. It should be unrolled fully or it will overheat and could catch fire.
- Make sure that any extension cable connections are

G THE FLOOR SCRUBBER DRYER

- e equipment including non-slip shoes m be worn
- 2. As with all el electrical equipment care and attention must ad at all times during use of the Floor Scrubber
- This floor cleaner is designed for operation by an able-bodied adult. Anyone with either temporary or permanent disability must seek expert advice before 3. . using it.
- Before performing the cleaning operation, place out appropriate warning sign(s), clear floor of debris, pick up pieces of wire, string, twine, etc., which could become wrapped around the scrub brush. Vacuum or dust-mop the floor.

- 5. This machine must not be used for picking-up hazardous dusts.
 - Do not allow the supply cord to come into contact with the rotating brushes. Keep a check on the position of the cable so that it does not get run over, stretched, or the plug is not accidentally pulled from the socket.
- Keep the cable clear of any sharp edges in the work 8.
 - If it appears that the cable may be cut or damaged in any way, switch off and unplug at the mains before inspecting it. If the cable attached to the floor cleaner is damaged, stop using the equipment. Contact the hire company. If an extension cable has been damaged, do not use it again.
- 9. Switch off and unplug from the socket before leaving the machine unattende ed. 10.
- When the work has been finished, empty any remaining cleaning solution and partly refill with clean water. Operate the machine in a safe place to flush the cleaning solution out of the equipment. Empty and rinse clean collection reservoir.
- Keep everyone, especially young children and the infirm, off the cleaned floor until it is dry. They cou 11. fall on the slippery surface.
- If the equipment does not work properly do not attempt to repair it. Contact the Hire Company. 12

44 (0) 121 380 4600

mail@hae.org.uk

www.hae.org.uk

In order to prevent unauthorised use of the machine in curds to prevent unauthorised use of the were source immediately following use. Machines left unaitended must be suitably secured to prevent unintentional movement (remove keys / engage brakes).

Check how the on/off switch operates. Before the floor cleaner is switched on it must be known how to stop it.

Electrical switches or plugs should not be touched

A range of different burahes, pada and oftenrická may be povided for different applications. These include cleaning, carubbing and polishing, contact the hite company if any of hase other accessionies are needed. **Note:** Do not leave the machine aristicating of huber pada when not in eas.

ne control arm is adjustable, set it to a comfortable ght. Make sure that it is locked into position.

Fill the solution tank with cold or warm water. Do not put hot water of a temperature likely to cause scalding into the clean water tank.

Read the instructions supplied with any cleaning chemicals which are to be used.

tel is if it a.esu in fort and yes monotonation to the surface it may boote or an a carpet or other sensitive surface it such inon' a periodic in the second monoton to the second second the second s

Answ. Equipment with a cylindrical yellow industrial plug Equipment with a cylindrical yellow industrial plug The plug end or on participation of a periable transformer if the equipment is to be powered from a vorsal standard with the equipment of the plug transformer if the equipment of the plug transformer if the equipment is to be powered from a roward standard or to the event that is the peers and institution of the maximum of the plug plug fruction of the plug plug fruction of the plug fruction of a horized to be plug.

Check that the plug on the equipment matches supply. Do not try to force connections or improv

Check the floor cleaner, cables, plugs and all of equipment. If anything is found to be damaged not use the cleaner – contact the hire company.

nuiezz usuaz sie ary.

-11

-8

-2

°C

.,

3

Before Starting Work...

Useful Reference Points • www.hae.org.uk/businessguard

Check the

HENDR CLEANER

eut t

Floor Scrubber-Dryer - Mains Powered

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read this entire leaflet BEFORE using the Floor Scrubber-Dryer. It is also important to observe all safety advisory labels and markings on the equipment prior to operating the equipment.

- This machine is for indoor use only.
- his machine is suited for commercial use, e.g. in hotels, schools, hospitals, facto hops, offices and rental companies. 2. Electricity can be hazardous and must always be used with great can
- Electricity and water can make a hazardous combination. Care must be taken whenever water or other solutions are used to keep them away from plugs, sockets, switches and the electrical parts of the cleaner. 4
- This floor cleaner is designed for cleaning, polishing and scrubbing hard surfar level floors that are not sensitive to moisture and polishing operations. appliance is not suited for the cleaning of frozen grounds (e.g. in cold stores).
- Only use brushes/pads provided with the appliance. The use of other brushes or accessories may impair safe brushes or pads which are suitable for the correct operation of the machine for the specific task being perfor with the Hire Company first. 6. air safety. Only use
- 7 The action of this floor cleaner can cause injury or damage to property if the equipment is misused
- Operators must be adequately instructed in the correct use of the machine. Operators must be suitably familiar with the equipment controls prior to use of the Floor Scrubber-Dryer. Controls may vary on different manufacturers machines therefore a working demonstration / familiarisation hand-over will be necessary in all instances where the operator has not used the Floor Scrubber-Dryer before. This shall include all necessary pre-use checks, filling and draining of any tanks, any daily routine operator maintenance requirements, all safety features and necessary guidance relevant to the tasks to be carried out including safe movement and storage of equipment, and with regard to the specific environment in which the equipment is to be used. Refer to manufacturers operating instructions for 8 further details.
- 9. Use only recommended detergents in accordance with the manufacturer's recommendations. Do not use highly foaming detergents. Consult the Hire Company for further information. The machine must not be used on inclines that exceed 2%.
- 10.
- Care must be taken to reduce speed when cornering or when manoeuvring around obstacles 11. 12.
- Avoid risk of damage when cleaning close to walls by ensuring deflection rollers point towards the wall (where fitted), or operate at a slower speed.

(Continued overleaf...)



ммм.рае.огд.ик

Personal Protective Equipment) that may be quired for certain operations:

damage to properly if the equipment is misused. Operators must be adequately instructed in the concert use of the machine. Operators must be address of the machine operators must be address of the machine operators must use of the Floor Scrubber-Dyser Controls may vary use of the Floor Scrubber-Dyser before. This has not used the Floor Scrubber-Dyser before. This has not used the Floor Scrubber-Dyser before. This million floating demonstration / tamiliarisation hand-over the address of the Hoor Scrubber-Dyser before. This has not used the Floor Scrubber-Dyser before. This puldance relevant to the tasks to be camed out relating of tamils, daily routine operator machine and treduing adarces relevant and scrage of optiment. The equipment is to be used. Contact the Hire company or relet to manufactures of equipment. Company or relet to manufactures operating the equipment.

asmage to property it the equipment is misused. The action of this floor cleaner can cause injury or

Non-slip safety footwear should be worn.

Anyone who is working nearby will also need to wear appropriate PPE and protective clothing.

Waterproof gloves should be worn if cleaning or other chemicals are to be handled.

You may need to check that the ear defenders or ear plugs you pick do not make things too quet. When ear hear important orders or elarms.

. പത്വമവ

Telephone: 44 (0) 121 380 4600

te: A risk assessment should termine which PPE should be wor

instructions for further details.

restriction frictionary without and addition and addition and addition addition additionary additionar

:eusdew

:lism∃

PPE (Perso

·9

·g

.4

3.

ry effort has been made by HAE/EHA to ensure that the information given in this document and supporting mat is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.



3YT TEB Iludilos The Crescent Birmingham Business Park nuo sinegen uct HILE ASSOCIATION EUROPE

West ear defenders or ear plugs (EN 352). You should pick ear defenders or ear plugs that can be shown to give enough protection to limit the risk of hearing loss. brotection.

(PPE) are the minimum that should be worn whenever the equipment is used. Particular jobs or environments may require a higher level of protection. owing items of personal protective equipment **SHOTAREGO**

.s

.91 **.**91

771

.51

- Find out where the electrical sockets are. Plan th work route around the floor so that the work can b done effectively, without running over the cable, c causing a tripping hazard. subis primew du
- caused by the work. Warn people to keep away. Pur Protect people from slippery floors or other hazards 3
- Make sure that the area is clear and safe and that no one is nearby so that the work can be done withou
- .s -Shinders.
- ot explosion. It will ignite tumes from petrol, or gas o not use this floor cleaner where there is a danger
 - **WORK AREA**
- 1 Guisr

This equipment array not be used by minors or by anyone hadden to find the or of drugs or drug or drug This 10or cleaner is designed for operation by an able-bodied adult, Anyone with either temporary or permanent resthilts water seek extra drugs helpre

whenever possible and state to do so. A minimum of the ollowing items of personal protective aquipment must be worn: Wear ear defenders or sar puge (tha 25). You should poly ear defenders or sar puge (tha 25). You should poly ear defenders or sar puge (tha that the risk of harming loss. You may need to check that the ask defenders or ear and environ sort make things too quiet. When that do hear to not make things too quiet. When weiterprot Glowes, low-silly Salety, Footwear, an REO if using a S30 voir (mains) supply. This aquipment must not be used by minors or by "This aquipment must not be used by minors or by

Avoid risk of damage to floor coverings. Do not operate appliance on the spot, keep moving

nenever possible and sale to do so.

- ισυσμία αιεσαρικλ μησε εσοκ σχόσι σαλικό ασιοιο