

GENERATOR SPECIFICATION

Voltage	230/115
Phase	1
Frequency	50Hz
Prime Power (PRP)	6.5kVA / 5.2kW
Alternator	NSM C100 SG
Alternator Type	Brushless - Smooth Waveform
Fuel tank capacity	6.1 Litres
Autonomy 75% load	2.2 Hours
LWA	97
dBA @ 7M	72

ENGINE SPECIFICATION

Engine	Honda GX390
Emissions certified	EU Stage V
Cylinders	Single
Distribution	O.H.V.
Aspiration	Naturally aspirated
Cooling	Air
Displacement	389 cm ³
Rpm	3000
Starting system	Recoil
Fuel	Unleaded 86 octane or higher



DIMENSIONS (mm)

DIMENSIONS (mm)			WEIGHT (KG)
Length	Width	Height	71
690	480	540	



HONDA
The Power of Dreams

CONTROL BOX

- 115V: 1 x 16A & 1 x 32A BS4343 sockets.
- 230V: 1 x 16A & 1 x 32A BS4343 sockets.
- Reset circuit breaker overload protection.
- Voltage selector switch.

STANDARD FEATURES

- Oil alert/low oil shutdown.
- 3 Year engine warranty (Limited).
- Full wrap-around frame.
- Brushless smooth waveform alternator.

OPTIONS

- AVR (Automatic Voltage Regulator).
- Electric start.
- Long run tank.
- Single voltage.
- Trolley kit.*

* Different model used to illustrate trolley option.



POWER DEFINITION

Prime Power (PRP) :

Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1.